



Page Number	551-093
Effective	Sept 2017
Replaces	Feb 2017
Section	551

<b>PART NAME</b>	<b>STANDARD MATERIALS</b>
Body, Cover	Ductile Iron: ASTM A536
Impeller	Bronze
Bearings	Ball , 'Sealed-for-Life'
Shaft	Carbon Steel
O-Rings:	FKM
<b>Mechanical Seals</b>	
Stationary O-Ring	FKM
Stationary Seat	Carbon
Rotating O-Ring	FKM
Rotating Seal Face	Ni-Resist
Seal Sleeve	Carbon Steel
Seal Cartridge	Ductile Iron: ASTM A536
Seal Spring	Stainless Steel
Coupling Guard	Aluminum
Gage Ports	1/4" NPT Inlet and Discharge

**PIPE CONNECTIONS**

<b>RC20, RC25</b>	1" NPT Tapped Ports
<b>RC40</b>	NPT and ANSI Class 300 Ports, 1.5 in (inlet) x 1 in (outlet)

**OPERATING LIMITS**

Maximum Differential Pressure	175 psi (12.1 Bar)
Maximum Working Pressure	350 psi (24.13 Bar) for LPG Service (Limited by U.L. and NFPA 58)
Minimum Temperature	-20°F (-29°C)